



Specification & Parameter:

Model		ZV-AHD1004M	ZV-AHD1008M	ZV-AHD1016M
System	Main processor	Hisilicon HI3515	Hisilicon HI3520	Hisilicon HI3531
Video	Video compression	H.264 (High Profile)		
	Encode Config	4*720P real-time	8*720P real-time	16*720P real-time
Audio	Audio compression	G.711A	G.711A	G.711A
	Intercom	support	support	support
Recording and Playback	Record mode	Manual> motion detection>timing		
	Playback	4*720P, 1080N	8*720P, 1080N	16*720P,1080N
Storage and backup	Hard disk	1 X SATA (Up to 6TB)	1 X SATA (Up to 6TB)	1 X SATA (Up to 6TB)
	Backup mode	USB HDD, USB writer	USB HDD, USB writer	USB HDD, USB writer
Interface	Video input/output	4 BNC (AHD DVR 4CH*720P@25fps) /1ch VGA,1ch HDMI, 1ch RCA	8 BNC (AHD DVR 8CH*720P@25fps) /1ch VGA,1ch HDMI, 1ch RCA	16 BNC (AHD DVR 16 CH*720P@25fps) /1ch VGA,1ch HDMI,1ch RCA
	Audio input/output	1ch RCA/1ch RCA	1ch RCA/1ch RCA	2ch RCA/1ch RCA
	Alarm input/output	NO	NO	NO
	Network interface	RJ45 10M/100M Adaptive Ethernet port	RJ45 10M/100M Adaptive Ethernet port	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	One RS485 ; support multiple PTZ protocols	One RS485 ; support multiple PTZ protocols	One RS485 ; support multiple PTZ protocols
	USB	1 USB port	1 USB port	1 USB port
	3G/WiFi	Support	Support	NO
Other	Power	12V2A	12V2A	12V2A
	Online View	PC (CMS and IE: DDNS /Cloud), Mobile. Max Support: 4*720P	PC (CMS and IE: DDNS /Cloud), Mobile. Max Support: 8*720P	PC (CMS and IE: DDNS /Cloud), Mobile. Max Support: 16*720P
	Mobile App Cloud Android & iOS	N_EYE (yunyis.com)	N_EYE (yunyis.com)	N_EYE (yunyis.com)
	Weight	2 KG	2 KG	2 KG
	Dimension	Unit size: 230mm* 260mm* 45mm	Unit size: 230mm* 260mm* 45mm	Unit size: 230mm* 260mm* 45mm