

ZUVOR

ZV-IP574F-1.3M

Bullet IP Camera Mega Pixel



Specification & Parameter:

| ModA4:D35 | ZV-IP574F-1.3M |
|------------------------|--|
| Image Sensor | HI3518E+SC1035 |
| TV System | PAL/NTSC |
| Image Resolution | 1280*960@25fps/ 1280*960@30fps |
| Horizontal Resolution | 1.3MP |
| Minimum illuminator | 0 .001Lux (Infrared Light Open) |
| Gama adjust | 0,45 |
| Infrared Sensitivity | Support |
| S/N Ratio | 58dB(min)(AGC closed) |
| Lens | 3.6 mm HD 3MP Lens |
| Leds | 30 pcs IR Led or 18pcs New High Brightness LEDs |
| DNR | Yes |
| BLC | ON/OFF |
| Day/Night | Yes |
| Compression Technology | H.264 Main Profile @level 3 |
| Max Coding Rate | 128-8192kbps |
| Encoding Type | CBR or VBR |
| R/N Ratio | More than 50DB |
| Image intensification | Brightness, Contrast, Saturation, HU Adjustable |
| Subtitle Input | Support Channels name, Date & time |
| Video Orientation | Left & Right Mirror, Up & down Flip |
| Audio input | Optional |
| Alarm | Motion Detection(Sensitivity adjustable) |
| Network Port | Ethernet(10M/100M Base-T),RJ45 |
| Safety | IP Address Filtering, User rank protect, User login log |
| Software management | CMS, Onvif support different platform software |
| Video Protocol | TCP,UDP,IP,HTTP,FTP,SMTP,DHCP,DNS,ARP,ICMP,POP3,NTP,R TP, and RTSP, Onvif2.0 |
| Network Port | Support DDNS, P2P(NAT),software remote access |
| Power Input | DC12V±1V |
| Operation Temperature | Temperature -10℃~+75℃,Humidity less than 85%RH |
| OSD Language | Chinese English |
| Dimension | 165(L) x59(W) x67(H)mm |
| Weight | 0.8KG |
| Video Output | 1.0Vp-p,75Ω |

